PATENT ABSTRACTS OF JAPAN

(11)Publication number:

64-082671

(43)Date of publication of application: 28.03.1989

(51)Int.CI.

H01L 29/78

H01L 21/318

(21)Application number: 62-242134

(71)Applicant: NEC CORP

(22)Date of filing:

25.09.1987


(72)Inventor: TATSUMI ASAKO

(54) MANUFACTURE OF MIS FIELD-EFFECT TRANSISTOR

(57)Abstract:

PURPOSE: To improve reliability and to reduce irregularities in characteristics by forming an oxide layer as a protective film against a resist developer on an AIN film in a MIS FET having AIN as a gate insulating film on a III-V compound semiconductor

CONSTITUTION: An n+ type layer 2 is formed by atomic layer epitaxial growth as a source and drain electrode contact layer on a semi-insulating InP substrate 1. Then, an AIN film 3 is formed as a gate insulating film by an organic metal vapor growing method on the substrate 1. Thereafter, the surface of the film 3 is exposed with an oxygen atmosphere at 100° C., thereby forming a surface oxide film 4 having 50Å of thickness. Subsequently, a photoresist pattern 5 for forming a gate electrode 6 is formed of positive type resist. Then, aluminum is deposited by a resistance heating method on the whole surface of a sample. Thereafter, the pattern 5 is removed to be lifted OFF, and a gate electrode 6 is formed. Then, it can prevent electric characteristics of the AIN and a boundary between the AIN and a semiconductor from being deteriorated with a resist developer.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]